Decoding PFAS Behaviour in soils: Evidence from three PARC case studies

14 October 2025, ENSOr conference

Laetitia Six & Griet Van Gestel (OVAM)

Ward Swinnen, Ilse Van Keer, Jan Jordens, Griet Jacobs & , Stefan Voorspoels, (VITO)

Adrian Covaci & Francesca Cappelli (UA)

Katrin Vorkamp (Ahrus university), Valeria Dulio (INERIS) and Georgios Niarchos (Swedish university of agricultural sciences)











Walk in the PARC?

PARC = Partnership for the Assessment of Risks from Chemicals

- A public-public partnership under Horizon Europe
- Co-fund budget
- Started 1st of May 2022 and has a duration of 7 years
- ≈ 200 partners from 29 countries
- Includes 3 European Agencies:













Work packages within PARC



Work package 4:




Task 4.2

- EDC campaign
- PFAS case studies
- PFAS baseline
- Prioritisation framework



Aim of PFAS Case Studies

To gain a better understanding of the PFAS fate and pathways from sources to aquatic recipients





PFAS case studies centred around 5 research questions

- What is the role of precursors?
- How far can PFAS precursors be transported?
- How do environmental conditions and PFAS molecular structures influence their transport?
- Can non-target methods contribute to establishing a "PFAS fingerprint", which might improve our understanding of pathways?
- Can fingerprinting be used for source identification and can it be embedded in monitoring?





EU PARC – 19 Case studies from 11 countries

PFAS Sources



















Environmental matrices













3 case studies from Flanders

1. PFAS mapping at former paper manufacturing site



2. PFAS leaching - Experimental determination of Kd values for PFAS in Flemish soils



3. NTA at PFAS-suspected locations












PFAS mapping at former paper manufacturing site








Data available from earlier soil investigations



Sample selection to investigate transport





- 6 clusters with increasing distance from former manufacturing site – 150 à 200 m steps
- sampled at 3 depths for soil and groundwater in the presumed groundwater flow direction:

• Depth 1: 2-3 m

• Depth 2: 5-6 m

Depth 3: 8-10 m

Target analysis: 42 PFAS of which 6 PFAS linear & total

• LOQ soil: 0,5 μg/kg

LOQ groundwater: 10 ng/L

Non-targeted analysis: DART + NTA



How do PFAS molecular structures influence transport?


PFAS mapping

HORIZONTAL

- Soil:
 - FoQ: PFOA, PFOS and 4:2 FTS have been detected at sampling depth 1.
 - O In deeper layers no PFAS detected (LOQ soil: 0,5 μg/kg)

Groundwater:

- 22 out of 42 PFAS detected.
- PFBA, PFOA, PFOS and PFHxA in > 75% of the samples
- Horizontal
 distribution –
 changes with
 distances from
 source







How do PFAS molecular structures influence transport?



HORIZONTAL

• Groundwater – depth 1, closest to paper manufacturing site:








How do PFAS molecular structures influence transport?




VERTICAL

Groundwater:

- Highest concentrations in upper layers, except for PFBS
- In general: Longer chain less observed in deeper layers










Groundwater in 3D


Groundwater – evolution with depth and distance














Fingerprinting with NTA

Good match!








Experimental determination of Kd values for PFAS



- Datasets of PFAS Koc-values are available in scientific literature, but:
 - Large variation in obtained results (soil types, climatic zones, ...)
 Variety of techniques to determine Kd-values (modelling, lab experiments, ...)
- Goal: determine Kd/Koc-values for PFAS for Flemish soils, including ultrashort chain PFAS.
- 26 soil samples from 25 sites, representative for PFAS in Flanders





Lab analysis



- Multiple soil samples at each sampling site
- Limited sampling depth (max. 4 meters below ground surface)
- Subselection of most "promising" sample based on DART-MS screening
- 24h leaching test (shaking) with 0.01M CaCl₂ and an L/S of 10
- Target PFAS analysis on the soil, and both the eluate and solid residue after the shaking test








- 48 target parameters analysed (42 PFAS with 6 PFAS linear & total)
- 7 additional ultrashort chain PFAS analysed in soil and eluate: TFA, 2,3,3,3-TeFPA, 2,2,3,3-TeFPA, PFPrA, TFMS, PFEtS, PFPrS
- Only Kd-values if both the soil/residue and eluate concentrations are above the LOQ


- Two variants of Kd-values calculated:
 - Soil / eluate concentrations
 - Solid residue / eluate concentrations







- Koc-values based on the measured organic carbon content
- $Koc = \frac{(K_d*100)}{\%OC}$
- Kd and Koc values for 37/48 target PFAS and 2/7 USC PFAS










General trend: Koc of soil/eluate is higher (up to one order of magnitude)

This effect is most significant at shorter chain lengths, due to more leaching





NTA (non-targeted analysis) at PFAS-suspected locations

 What does the PFAS fingerprint look like at different sites and how does this correspond to the PFAS source?



- Selection of PFAS contaminated sites (33 sites):
 - Textile industry (3 sites)
 - Firefighting and fire-related contamination (21 sites)
 - Paper manufacturing (2 sites)
 - Metal plating (e.g. chromating) (4 sites)
 - Waste recycling (2 sites)
 - PFAS production (1 site)





Analytical approach





Selection of most promising samples for further analysis

AOF / EOF


Non-target analysis (NTA)


Capture total organofluorine burden


Non-target analysis (NTA)

I

lonic unknown PFAS










Selection of most promising samples: DART-MS

PFAS

NTA

at PFAS-suspecte
locations

- DART-MS can be used to
 - Select samples out of multiple repeats
 - Select samples based on the estimated amount of PFAS
 - Select samples for NTA or only target analysis
 - Show depth and horizontal profiles





Similar source of contamination shows different


fingerprints

Fingerprinting fire-related sites



We can't generalise that each PFAS pressure has its typical fingerprint.

For example: different fingerprints observed for fire-related contamination






Use of fingerprints to determine contamination source



NTA all PFAS

At one location and with a known source, fingerprints can be used to link pollution to the site of origin





Other remarks



Added value of TOPA could not be demonstrated for soil: technical developments needed?

DART <-> LC (target/NTA) correlation seems to be better than correlation between LC and TOPA or EOF/AOF

DART is not universal yet, but provides added value



Many thanks

